## **SPECIFICATIONS** MAX VOLTAGE - 600VAC 3Φ **DEAD-FRONT CURRENT RANGE - 500-800A** PANEL-STANDARDS - UL508A EMERGENCY HANDLE SUITABLE FOR USE AS SERVICE EQUIPMENT **ENCLOSURE RATING - NEMA 3R** REF ES11BTS3A EST SHIPPING WEIGHT - 650 LBS **TOP VIEW** 36" NORMAL HANDLE **SERVICE DISCONNECT** FRONT VIEW REMOVED "NORMAL" BREAKER (SERVICE ENTRANCE) (4) 4/0-500MCM 65kAIC @ 480V PADLOCKABLE DOOR HANDLE **NEUTRAL LUGS** "EMERGENCY" (4) #2-750MCM BREAKER (4) 4/0-500MCM 65kAIC @ 480V DISCONNECT LINK ~ "LOAD" **DISTRIBUTION SIDE VIEW FRONT VIEW SIDE VIEW** (4) #2-600MCM GROUND LUGS (1) #6-350MCM FRONT VIEW DOOR/DEADFRONT REMOVED NOTE: BREAKERS ARE MECHANICALLY INTERLOCKED BY A WALKING BEAM MECHANISM. ONLY ONE 500-800A BREAKER-BREAKER TRANSFER SWITCH **CAN BE ENERGIZED AT A TIME** REV DESCRIPTION DATE DRAWN S.RICHARDSON O ORIGINAL RELEASE 2/8/17 CHECKED **DIMENSIONAL** 9900 TWIN LAKES PARKWAY CHARLOTTE, NC 28269 704-596-5617 PANEL NO **BOTTOM VIEW** BUL. NO BTS800N3RDSE3A GROUP NO PSICONTROLSOLUTIONS.COM