



SPECIFICATIONS

MAX VOLTAGE - 600VAC 3Φ
 RATED CURRENT - 100A
 STANDARDS - UL508A
 ENCLOSURE RATING - NEMA 4
 REF. ES11NFD3
 ENDURANCE - 8000 CYCLES
 EST. SHIPPING WEIGHT - 100LBS




TOP VIEW




DETAIL A
 SCALE 1 : 2

CONNECTIONS


L1/L2/L3 - #6-300MCM
 T1/T2/T3 - #6-300MCM
 N - #14-1/0 AWG
 G - #14-1/0 AWG




SIDE VIEW




FRONT VIEW



SIDE VIEW



FRONT VIEW
 DOOR REMOVED



BOTTOM VIEW

NOTES

1: NEUTRAL KIT ONLY PRESENT IF PURCHASED



9900 TWIN LAKES PARKWAY
 CHARLOTTE, NC 28269
 704-596-5617
 PSICONTROLSOLUTIONS.COM

100A ENCLOSED NON-FUSIBLE DISCONNECT NEMA 4			
REV	DESCRIPTION	DATE	DRAWN S.RICHARDSON
0	ORIGINAL RELEASE	11/14/16	CHECKED
			SUP. NO
			SUP. BY NO
			PANEL NO
			BUIL. NO
			GROUP NO
			ORDER NO

DRAWING TYPE	DIMENSIONAL
DRAWING NUMBER	NFD100N4