



SPECIFICATIONS

MAX VOLTAGE - 600VAC 3 ϕ
 RATED CURRENT - 2500 A
 IEC RATED ONLY - NO UL LISTING
 ENCLOSURE RATING - NEMA 3R
 REF. ES100145BF
 DURABILITY - 3000 CYCLES
 EST SHIPPING WEIGHT - 1050LBS



TOP VIEW

36" ENCLOSURE WIDTH



SIDE VIEW


"NORMAL SUPPLY" (GREEN)

"EMERGENCY SUPPLY" (RED)


PADLOCKABLE HANDLE I-O-II

PADLOCKABLE DOOR HANDLE


DRAIN PLUG




FRONT VIEW



SIDE VIEW



DIMETRIC VIEW




BOTTOM VIEW

2500A FUSIBLE 3-POLE NEMA 3R MANUAL TRANSFER SWITCH


REV	DESCRIPTION	DATE	DRAWN	S.RICHARDSON	CHECKED
0	ORIGINAL RELEASE	3/21/14			
				SUP. NO	
				SUP. BY NO	
				PANEL NO	
				BUL. NO	
				GROUP NO	
				ORDER NO	

DRAWING TYPE
DIMENSIONAL


DRAWING NUMBER
STS2500N3RBF3



9900 TWIN LAKES PARKWAY
 CHARLOTTE, NC 28269
 704-596-5617
 PSICONTROLSOLUTIONS.COM



FRONT VIEW
DOOR REMOVED



FRONT VIEW
ENCLOSURE REMOVED


"EMERGENCY"
CONNECTIONS
(REAR)

"NORMAL"
CONNECTIONS
(FRONT)

NEUTRAL LUGS
(6) #2-750 MCM


NEUTRAL
DISCONNECTING
MEANS

GROUND LUGS
(1) #2-750 MCM



DIMETRIC VIEW
DOOR REMOVED

NOTE:FUSES PROVIDED IF PURCHASED
208-600VAC : KRP-C-2500SP



2500A FUSIBLE 3-POLE NEMA 3R MANUAL TRANSFER SWITCH

REV	DESCRIPTION	DATE	DRAWN	S.RICHARDSON	CHECKED
0	ORIGINAL RELEASE	3/21/14			
			SUP. NO		DRAWING TYPE
			SUP. BY NO		OUTLINE
			PANEL NO		DRAWING NUMBER
			BUL. NO		STS2500N3RBF3
			GROUP NO		
			ORDER NO		