



SPECIFICATIONS


MAX VOLTAGE - 600VAC 3Φ
 RATED CURRENT - 400A
 STANDARDS - UL508A
 ENCLOSURE RATING - NEMA 4
 EST. SHIPPING WEIGHT - 150LBS



TOP VIEW




SIDE VIEW




FRONT VIEW

POWER ON

ROTARY DISCONNECT HANDLE
(SERVICE DISCONNECT)




SIDE VIEW



BOTTOM VIEW

CONNECTIONS

L1,L2,L3 - (2) 2/0-250MCM / (1) 2/0-500MCM
 T1,T2,T3 - (2) 2/0-250MCM / (1) 2/0-500MCM
 N - (2) 1/0-250MCM / (1) #2-750MCM
 G - #6-350MCM



FRONT VIEW
DOOR REMOVED

BREAKER
 400A FRAME
 400A TRIP
 65kAIC @ 480V



9900 TWIN LAKES PARKWAY
 CHARLOTTE, NC 28269
 704-596-5617
 PSICONTROLSOLUTIONS.COM

400A, 3-POLE ENCLOSED BREAKER NEMA 4 ROTARY HANDLE

REV	DESCRIPTION	DATE	DRAWN	S.RICHARDSON	
0	ORIGINAL RELEASE	8/2/17	CHECKED	J.RAY	
			SUP. NO		DRAWING TYPE
			SUP. BY NO		DIMENSIONAL
			PANEL NO		DRAWING NUMBER
			BUIL. NO		ECB400RN4SE3
			GROUP NO		
			ORDER NO		