



Emergency Power Products Powerful Results

Address: 9900 Twin Lakes Parkway
Charlotte,
NC 28269

Phone: 704-596-5617

Website: www.psicontrolsolutions.com Email: sales@psicontrolsolutions.com

Load Bank Docking Station or Generator Docking Station "GTBCB"

Rotary Handle mounted on dead front behind enclosure door. Molded Case Circuit Breaker standard 65kAIC @ 480 Volts NEMA 3R or 3RSS Enclosure with Drip Shield - 50" H x 17" W x 20" D

PSI Control Solutions, Inc 9900 Twin Lakes Parkway Charlotte, NC 28269

Phone: 704-596-5617

Website: www.psicontrolsolutions.com Email: sales@psicontrolsolutions.com



cETLus Listed to UL standard 1008 200-800 Amps



Features

- NEMA 3R ENCLOSURE OR NEMA 3RSS 316 STAINLESS STEEL ENCLOSURE
- ANSI-61 GRAY FOR NEMA 3R
- BREAKER OPERATION HANDLE LOCKABLE
- SWITCH RATED FOR ON-LOAD SWITCHING
- NEUTRAL AND GROUND BAR INCLUDED
- PILOT LIGHT INDICATION FOR VOLTAGE PRESENT
- RATED THROUGH 600VAC
- 1 PHASE 3 WIRE OR 3 PHASE 3 OR 4 WIRE
- 3 POLE BREAKER 65KAIC @ 480 VOLTS
- BREAKER HANDLE MOUNTED ON DEAD FRONT AND ENCLOSURE DOOR IS LOCKABLE
- BUS BAR SHALL BE SIZED 1000A/SQ INCH
- LUGS ARE SIZED AT 125% OF RATED AMPS
- 100% TESTED AT FULL VOLTAGE
- OPTIONAL PHASE REVERSAL PROTECTION RELAY

Part Number Structure Table

Product Type	Ampacity	Enclosure Rating	Cam- Locks	Voltage	Option Phase Relay
GTBCB	200 400 600 800	3R 3RSS	Female Male	208-240 480 480/277 575-600	None 208-480V 575-600V